

ECO-INDICATOR

Confirm system operation and adequate pressure with this handy visual device.

KEY BENEFITS

- Visible bright yellow or reclaimed purple riser stem and cap indicate when system is in operation
- Stem pops up when pressure exceeds the threshold and assists in confirming low pressures if not raised
- Connects via bottom or side inlet ports for easy installation; side inlet port is available on 30 cm version

OPERATING SPECIFICATIONS

- ECO-ID:
 - Operating pressure: up to 5 bar; 500kPa
 - Indication of system operation: above 0.8 bar; 80kPa
 - Warranty period: 2 years
- ECO-ID-12/ECO-ID-12-R:
 - Operating pressure: up to 7 bar; 700kPa
 - Indication of system operation: above 1 bar; 100kPa
 - Warranty period: 5 years

USER-INSTALLED OPTIONS (FOR 30 CM ECO-INDICATOR)

- Drain check valve (up to 3 m of elevation: P/N 437400SP)
- SJ Swing Joint: SJ-512 (½" threaded x 30 cm length)

ECO-INDICATOR	
Model	Description
ECO-ID	15 cm Eco-Indicator
ECO-ID-12	30 cm Eco-Indicator
ECO-ID-12-R	30 cm Eco-Indicator, Reclaimed

Eco-Indicator Installed



ECO-ID

Retracted height: 24 cm
Pop-up height: 15 cm
Exposed diameter: 3 cm
Inlet size: ½"




[A] ECO-ID-12


[B] ECO-ID-12-R

Retracted height: 41 cm
Pop-up height: 30 cm
Exposed diameter: 5.7 cm
Inlet size: ½"


Compatible with:



Eco-Mat™
System



Eco-Wrap™
System



HDL and PLD
Dripline